

Reading a ForteWEB Report (Link)

The structural analysis below is an example of a member report from single-member design software developed by Weyerhaeuser. Allowable design properties for products are in accordance with code approved values for current Weyerhaeuser materials. **The input loads and dimensions have been provided by others and must be verified and approved for the specific application by the design professional responsible for the project.**




MEMBER REPORT

Level, Floor: Joist

1 piece(s) 11 7/8" TJI® 210 @ 12" OC

1 PASSED

Overall Length: 25' 10 1/2"



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.

Design Results	Actual @ Location	Allowed	Result	LDf	Load: Combination (Pattern)
Member Reaction (lbs)	386 @ 3 1/2"	1005 (1.75")	Passed (38%)	1.00	1.0 D + 1.0 L (Alt Spans)
Shear (lbs)	453 @ 15' 3 1/2"	1821	Passed (25%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1241 @ 6' 8 11/16"	3795	Passed (33%)	1.00	1.0 D + 1.0 L (Alt Spans)
Live Load Defl. (in)	0.092 @ 7' 3"	0.379	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
Total Load Defl. (in)	0.149 @ 7' 2 7/8"	0.757	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
TJ-Pro™ Rating	56	40	Passed	--	--

System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A structural analysis of the deck has not been performed.
- Deflection analysis is based on composite action with a single layer of 23/32" Weyerhaeuser Edge™ Panel (24" Span Rating) that is glued and nailed down.
- Additional considerations for the TJ-Pro™ Rating include: 1/2" Gypsum ceiling.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 7/8" LVL beam	3.50"	Hanger ¹	1.75" / 1.75" ²	144	259	403	See note ¹
2 - Stud wall - HF	3.50"	3.50"	3.50"	278	527	805	None
3 - Stud wall - HF	3.50"	2.25"	1.75"	20	144/55	164/35	1 1/4" Rim Board

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.
- ² Required Bearing Length / Required Bearing Length with Web Stiffeners

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 9" o/c	
Bottom Edge (Lu)	6' 9" o/c	

- TJI joists are only analyzed using Maximum Allowable bracing solutions.
- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie						
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Top Mount Hanger	ITS2.06/11.88	2.00"	4-10dx1.5	2-10dx1.5	2-Strong Grip	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 8' 6"	12"	20.0	40.0	Residential Floor Loads - Living Areas (Bathroom)
2 - Uniform (PSF)	8' 6" to 25' 10 1/2"	12"	12.0	30.0	Residential Floor Loads - Sleeping Areas
3 - Point (PLF)	8' 6"	12"	64.0	-	Perpendicular Wall Weight

Holes (Size)	Width	Height	Vertical Offset	Location	Shear (lbs)			Comments
					Actual	Allowed	Result	
1 - Circular (L)	8.00"	8.00"	5 15/16"	10'	244	424	Passed (58%)	HVAC Hole

- Hole locations are measured from the outside face of left support (or left cantilever end) to the centerline of the hole.
- Vertical Offset is measured from the top of the member to the centerline of the hole.

Notch Type	Flange	Length	Depth	Location	Compression Moment (Ft-lbs)			Tension Moment (Ft-lbs)			Comments
					Actual	Allowed	Result	Actual	Allowed	Result	
Along Side	Top	3 1/2"	3/4"	8'	1192	2321	Passed (51%)	0	1338	Passed (0%)	Plumbing Waste Line Notch

- Notches are not allowed on adjacent joists.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by 3D's General Contracting

ForteWEB Software Operator	Job Notes
John Doe Lumber Co. (555) 123-5555 johndoe@lumberco.com	Smith's Residence 123 Any Street New York, NY 10001 Project #12345



7/25/2022 3:28:22 PM UTC
ForteWEB v3.4, Engine: V8.2.2.122, Data: V8.1.2.2
File Name: Forte Explanation

- Analysis result (Passed or Failed).
- Product analyzed including number of plies, joist depth, product type, and o.c. spacing.
- Span dimensions and conditions including simple spans, continuous spans, and cantilevers.
- System design information including building code and design methodology.
- Design results including member reaction, shear, moment, live load, and total load deflection, and TJ-Pro Rating (when applicable).
Actual @ Location: critical design values occur using the displayed load combination and pattern.
Allowed: maximum design values for the member and parameters selected.
Result: ($\leq 102\%$) member is sufficient to withstand applied loads.

- Deflection criteria
Live Load (LL)
Total Load (TL)

- Additional design considerations including composite action and TJ-Pro Rating.

- Support information including support type/condition, bearing length, loads to support, and accessories.

- Lateral bracing maximum distance between bracing points (compression edge) to prevent rotation/buckling.

- Load information including load type (uniform, tapered, point-PLF, etc.), location, spacing, classification (live load, dead load, roof live, etc.), and load duration factor.

- Hole information including shape, size, vertical offset, horizontal location, shear reduction, and results.

- Notch flange information including notch type, size, location, and design results.

- ForteWEB software operator information

- Job notes input typically includes project information.